




Cordless Hand Scanner *Series 7*

With Bluetooth® Wireless Technology

Specification Sheet

PHYSICAL CHARACTERISTICS

	CHS 7E <i>Entry Level</i> 	CHS 7M <i>Mid-Range</i> 	CHS 7P <i>Performance</i> 
Dimensions	125 x 31 x 35 mm (4.9 x 1.2 x 1.4 inches)		
Total Mass	51 g (1.8 oz)	51 g (1.8 oz)	approx. 68 g (2.4 oz)
Ruggedized Case	No	No	Yes. Withstands multiple 5-foot drops to concrete. Dust, shock, and water-resistant

ENVIRONMENTAL SPECIFICATIONS

	CHS 7E <i>Entry Level</i>	CHS 7M <i>Mid-Range</i>	CHS 7P <i>Performance</i>
Operating Temperature	+32 to +140°F (0 to +60°C)	-4 to +140°F (-20 to +60°C)	
Storage Temperature	-22 to +158°F (-30 to +70°C)	-40 to +158°F (-40 to +70°C)	
Relative Humidity	5% to 95% non-condensing		
Ambient Light	0.5 ft. candles (5 lux) to 8,000 ft. candles (86,112 lux)	Sunlight: 10,000 ft. candles (107,640 lux) Artificial light: 450 ft. candles (4,844 lux)	

ELECTRICAL SPECIFICATIONS

	CHS 7E <i>Entry Level</i>	CHS 7M <i>Mid-Range</i>	CHS 7P <i>Performance</i>
Power Source	Two AAA NiMH rechargeable batteries		
Expected Battery Life	Typical usage conditions with <i>Bluetooth</i> connection: 8,000+ scans		
Laser Power (650 nm)	N/A	0.7 mW (±0.1 mW)	1.7 mW (±0.2 mW)

Cordless Hand Scanner *Series 7*

With Bluetooth Wireless Technology

Specification Sheet

SCANNER PERFORMANCE SPECIFICATIONS			
	CHS 7E <i>Entry Level</i>	CHS 7M <i>Mid-Range</i>	CHS 7P <i>Performance</i>
Scanner Type	Symbol CSE600 CMOS linear imager	Symbol SE-955 Class 1 laser	Symbol SE-955 Class 2 laser
Types of Bar Codes Decoded	Linear (1D)	Linear (1D), Stacked linear composite (RSS-14)	
Symbologies Decoded	Codabar, Code 11, Code 128, Code 39, Code 93, D 2 of 5, I 2 of 5, MSI, UPC/EAN, Webcode	Same as CHSC 7E (except Webcode) plus Chinese 2 of 5, RSS-14/Limited/Expanded	
Scan Repetition Rate	Frame rate varies with the amount of ambient light	100 scans/sec bi-directional	
Optical Resolution	N/A	0.004 inch (0.102 mm) minimum/bar code element width (X Dimension)	
Print Contrast	35% MRD measured at 675 nm	Minimum 25% absolute dark/light reflectance (MRD) measured at 650 nm	
Scan Angle	N/A	Wide (default): 47° ±3° Narrow: 35° ±3°	
Decode Distance*	3.18 to 60.96 cm (1.25 to 24.00 inches) typical	2.50 to 88.90 cm (1.00 to 35.00 inches) typical	2.50 to 114.30 cm (1.00 to 45.00 inches) typical
LED/Laser Safety	EN60825 Class 1 LED	IEC60825-1 Class 1 laser	IEC60825 Class 2 laser

BLUETOOTH SPECIFICATIONS	
Interface Standard	<i>Bluetooth</i> Serial Port Profile
<i>Bluetooth</i> Protocol	<i>Bluetooth</i> 1.1: 2.4 to 2.4835 GHz ISM band frequency hopping
Antenna Type	Integrated
Radio Range	Class 1 <i>Bluetooth</i> : Up to 330 ft (100 m), depending on environment
Connection	Point to point
Compatibility	Windows COM port, <i>Bluetooth</i> QD ID B0164000
Security	128 bit encryption
Typical Output	12 dbm
Supported <i>Bluetooth</i> Stacks for Windows	Socket Mobile Drakar 1.4 IVT BlueSoleil 1.6.1.4 Broadcomm (Widcomm)1.4 Microsoft <i>Bluetooth</i> stack for Windows Mobile Microsoft Windows XP SP2 Toshiba <i>Bluetooth</i> stack 3.03.06 and greater for Windows XP



mobile

Cordless Hand Scanner *Series 7*

With Bluetooth Wireless Technology

SOFTWARE COMPATIBILITY

Operating System Support	Windows Mobile 2003/2003SE/ 5.0, Windows XP/XP Tablet Edition, Palm OS 5.2 or greater, Symbian Series 60/80
--------------------------	---

INCLUDED SOFTWARE AND HARDWARE

Included Software	Installation Utility; SocketScan for Windows Mobile, WindowsXP/XP Tablet Edition, Palm OS, Symbian OS; Connect!Agent for Windows Mobile and Windows XP/XP Tablet Edition; Socket Floating Trigger
Package Contents	Cordless Hand Scanner Series 7; AC charger with plugs for USA, Europe, UK, Australia; 2 NiMH rechargeable AAA batteries; CD with software and user documentation; lanyard/belt clip with retractable tether

OPTIONAL ACCESSORIES

	CHS 7E <i>Entry Level</i>	CHS 7M <i>Mid-Range</i>	CHS 7P <i>Performance</i>
Scanning Companion	USB <i>Bluetooth</i> adapter completes your CHS Series 7 by enabling you to operate with any notebook, tablet or desktop computer running Windows XP Service Pack 2 (SP2) with a USB slot. Available separately, SKU# BL4543-734		
Charging Cradle	N/A	N/A	Available for CHS 7P only SKU# AC4026-708

WARRANTY, REGULATORY COMPLIANCE

Warranty	Scanner: One year Accessories: 90 days SocketCare enhanced service program available separately		
Certification/Compliance	FCC: Part 15, Class B, CE: EN55024:2003, C-TICK: s.182, RoHS	FCC: Part 15, Class B, CE: EN55024:2003, IEC60825-1:1993 +A1:1997 +A2:2001, Japan VCCI, C-TICK: s.182, RoHS	

SKU NUMBERS

	CHS 7E <i>Entry Level</i>	CHS 7M <i>Mid-Range</i>	CHS 7P <i>Performance</i>
SKU #	CX2804-493	CX2800-489	CX2821-656



Sales Offices

Corporate Headquarters:
39700 Eureka Drive
Newark, CA 94560 USA

Web: www.socketmobile.com

Phone: +1-510-933-3000

USA & Canada Toll Free: 800-552-3300

Fax: +1-510-933-3030

Online: www.socketmobile.com/contact

© 2008, Socket Communications, Inc. dba Socket Mobile, Inc. Socket, the Socket logo, Cordless Hand Scanner, SocketScan, Connect!Agent, and Increasing Mobile Productivity are registered trademarks or trademarks of Socket Communications, Inc. dba Socket Mobile, Inc. The Bluetooth wordmark and logo are registered trademarks of the Bluetooth SIG, Inc. USA and any use by Socket Mobile, Inc. is under license. All other brand and product names are trademarks of their respective holders. 6450-00154F 1/2008